

8-port 1000Mbps Ethernet Switch (Plastic Shell)



Product Highlights:

- 8*1000Mbps RJ45 ports
- Compliant with IEEE802.3 and IEEE802.3u, IEEE802.3az, IEEE802.3ab standards
- RJ45 port supports 100/1000Mbps adaptive
- Supports automatic port flipping (Auto MDI/MDIX)
- The panel indicator lights will monitor the working status and assist in fault analysis
- Flow control method, IEEE802.3x standard for full duplex and Backpressure standard for half duplex

Hardware Features:

Description	Specification
Model	1G08-AT
Interface	8 *1000Mbps RJ45 ports
Port Standard	IEEE802.3 (Ethernet) IEEE802.3u (Fast Ethernet) IEEE802.3x (Flow Control) IEEE802.3ab (Gigabit Ethernet) IEEE802.3az(Energy Efficient Ethernet)
Switching Capacity	16Gbps
Packet Forwarding Rate	11.9Mpps
Packet Buffer	4Mbit
MAC Address Table	8K
Transmission Method	Store and Forward
Power Supply	AC 100-240V,50/60Hz DC 5V 1A
Mainboard Power Consumption	3.77W



8-Port 1000Mbps Ethernet Switch (Plastic Shell)

atop®

Technical Data Sheet

Structure Information

Product Dimensions:145*60*21.5mm
Packaging Dimensions:146*88*50mm

Product Net Weight:0.111Kg
Product Gross Weight:0.166Kg

Packing Information

Carton Dimensions:530*475*315mm
Packing Quantity: 100PCS
Packing Weight:17.6KG

Package Contents

switch 1pcs, Power adapter 1pcs, manual 1pcs, certificate of qualification

Fan Quantity

1pcs

0

Installation

desktop

Surge Protection

Operating Temperature

0~40°C

Storage Temperature

-40°Cto 70°C

Operation Humidity

10%~90%, non condensing

Storage Humidity

5%~95%, non condensing

PWR

On: Powered on

1-8 port

On: Link normal

Off: Link blocked

Blinking: Data transmitting

Off: Powered off

Product Structure Diagram:

